

LaceLok™ Cable Lacing Fastener

Specifications

Description	
Fastener Physical Dimensions (nominal)	
Length (A)	0.276 in. (7.01mm)
Width (B)	0.230 in. (5.84mm)
Height (C)	0.175 in. (4.44mm)
Weight	0.0095 oz. (0.269g)
Overall Length	6 - 44 in. (152-1118mm)
Construction	
Fastener Head	Ultra high temperature thermoplastic, UV resistant black
Lace	NOMEX® White
Environmental	
Operating Temperature	-76°F to 392°F (-60° to 200°C)
Chemical Resistance	Hydraulic fluid, jet fuel, lubricating oil, isopropyl alcohol
Standards & Specifications	
Lace meets MIL SPEC A-A52084 Size 2 Finish C; Cable Lacing Fastener compliant with MIL SPEC: Pending; Must be installed using IDEAL Installation Tool	

Nomex® is a registered trademark of E.I. du Pont de Nemours and Co.

Ordering Information

Description	Qty.	Part No.
LaceLok™ Cable Lacing Fastener Tool	—	41-499
6 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 10,000	10,000/Carton	M4-1-06-C
6 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 500	500/Bag	M4-1-06-B
10 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 10,000	10,000/Carton	M4-1-10-C
10 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 500	500/Bag	M4-1-10-B
18 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 5,000	5,000/Carton	M4-1-18-C
18 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 500	500/Bag	M4-1-18-B
24 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 5,000	5,000/Carton	M4-1-24-C
24 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 500	500/Bag	M4-1-24-B
44 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 2,500	2,500/Bag	M4-1-44-C
44 in. LaceLok™ Cable Lacing Fastener White Lace w/Black Head; 250	250/Bag	M4-1-44-B
6 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 10,000	10,000/Bag	M4-2-06-C
6 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 500	500/Bag	M4-2-06-B
10 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 10,000	10,000/Bag	M4-2-10-C
10 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 500	500/Bag	M4-2-10-B
18 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 5,000	5,000/Bag	M4-2-18-C
18 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 500	500/Bag	M4-2-18-B
24 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 5,000	5,000/Bag	M4-2-24-C
24 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 500	500/Bag	M4-2-24-B
44 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 2,500	2,500/Bag	M4-2-44-C
44 in. LaceLok™ Cable Lacing Fastener Black Lace w/Black Head; 250	250/Bag	M4-2-44-B



**LaceLok™
Cable Lacing Tool**

- LaceLok™ Cable Lacing Fasteners have a tensile strength as listed below: single wrap – 39 lbs, double wrapped – 98 lbs. and triple wrapped – 164 lbs.
- 6 in. Cable Lacing Fastener used for single wrap bundles up to 1 in. (25.4mm)
- 10 in. Cable Lacing Fastener used for double wrap bundles up to 1 in. (25.4mm)
- Installing 1,000 doubled wrapped LaceLok™ Fasteners save 1 lb. versus 1,000 MIL-SPEC 50 lb. tensile strength nylon cable ties